

# 4FE42



4" - 40 W - 94 dB - 8 Ohm

## NOMINAL SPECIFICATIONS

Nominal Diameter	100 mm (4 in)
Overall Diameter	129.85/100.5 mm (5.11/3.96 in)
Bolt Circle Diameter	115.26 mm (4.54 in)
Baffle Cutout Diameter	91.5 mm (3.60 in)
Depth	54.1 mm (2.13 in)
Flange and Gasket Thickness	7 mm (0.28 in)
<b>Net Weight</b>	<b>390 g (0.9 lb)</b>
Shipping Box (Single Carton Box - 8 units)	225 x 225 x 150 mm (8.9 x 8.9 x 5.9 in)
Shipping Weight (8 units)	3.6 kg (7.9 lb)

## PART NUMBER

Faston Terminals - 8 Ohm Version	01004370
----------------------------------	----------

## NOTES:

Packaged and sold in multiples of 8 units

(1) 2 Hours Test According to AES 2-1984 Rev. 2003

(2) Maximum power is defined as 3dB greater than nominal power.

(3) NBR (Rubber)

(4)  $X_{max} = [(winding\ depth - magnetic\ gap\ depth)/2] + (magnetic\ gap\ depth/3)$

(5) Maximum excursion before permanent damage

## TECHNICAL PARAMETERS

Nominal Impedance	8 Ohm
Minimum Impedance	6.2 Ohm
AES Power Handling (1)	40 W
<b>Maximum Power Handling (2)</b>	<b>80 W</b>
<b>Sensitivity (1W/1m)</b>	<b>94 dB</b>
Frequency Range	100-20000 Hz
<b>Voice Coil Diameter</b>	<b>25 mm (0.98 in)</b>
Winding Material	Al
Former Material	Kapton
Winding Depth	7 mm (0.28 in)
<b>Magnetic Gap Depth</b>	<b>4 mm (0.16 in)</b>
Flux Density	1.4 T
Magnet	Neodymium Ring
Basket Material	Steel
Demodulation	Copper Cap
Cone Surround (3)	Half Roll
NET Air Volume filled by Loudspeaker	0.105 dm <sup>3</sup> (0.004 ft <sup>3</sup> )
Spider Profile	1x constant height waves

## THIELE & SMALL PARAMETERS

Fs	110 Hz
Re	5.4 Ohm
Qes	0.50
Qms	8.0
Qts	0.47
Vas	1.9 dm <sup>3</sup> (0.07 ft <sup>3</sup> )
Sd	50.9 cm <sup>2</sup> (7.89 in <sup>2</sup> )
Xmax (4)	2.83 mm
Xdamage (5)	5.1 mm
Mms	4.0 g
Bl	6 N/A
Le	0.07 mH
Mmd	3.6 g
Cms	0.52 mm/N
Rms	0.3 kg/s
Eta Zero	0.59 %
EBP	220 Hz

